

AV-1500

SIP-Ready Multi-Biometric Access Control



Facial
Authentication




RFID



IP65 dust &
waterproof rating



Video Intercom
(SIP)



Introduction

AV-1500 adopts the latest intelligent engineering facial authentication and technology. facial, card authentication with large capacity and speedy authentication, adopts ultimate antispooing algorithm for facial authentication against almost all types of fake photos and videos attack, which offering secure biometric authentication. AV-1500 is an access control terminal featuring a video intercom function and supports ONVIF protocol. It fully improves the video intercom experience and can be compatible with video intercom indoor unit with SIP protocol (Version 2.0).

Besides, AV-1500 supports multiple communication protocols. Its has AC push and can convert to TA push and it is compatible with various AC or TA software.

Key Features


- Visible Light Facial Authentication Technology
- Attained IP65 Protection Rating With Dustproof and Waterproof
- Multiple Authentication Methods: Facial / RFID / Password
- Available RFID Modules: 125 kHz ID Card / 13.56 MHz IC Card
- HD Video Door Phone Via SIP Protocol (Version 2.0)
- User Data Synchronization: User data can be downloaded/uploaded from one device to another via a USB drive Compatible with wireless doorbell (optional).
- Advanced access control functions (Wiegand input or output shared; RS485 communication; Electric Lock; Door Sensor; Exit Button).




Specifications

Model	AV-1500
Display	4.3"@ TFT Color Touch LED Screen (272*480)
Camera	WDR Binocular Camera @ 1MP
Operation System	Linux
Hardware	CPU: Dual Core@1GHz RAM: 512MB; ROM: 8GB Speaker: 8ohm @1W Microphone: *1 (Sensitivity: -42 dB/ Omni-directional/ Signal-to-Noise Ratio: 58 dB/ Impedance: 2.2kΩ) Supplement Light: No
Authentication method	Face / Card / Password (Virtual Keypad)
Face Template Capacity	1,500 (1:N) (Standard)
Card Capacity	1,500 (1:N) (Standard)
User Capacity	1,500 (1:N) (Standard)
Transaction Capacity	200,000 (1:N)
Max. User Password Length	8 Digits
Biometric Authentication Speed	less than 0.35 sec (Facial Authentication)
Touchless Biometric Authentication Distance	30cm to 200cm (Facial Authentication)
False Acceptance Rate (FAR) %	FAR ≤ 0.01% (Visible Light Facial Authentication)
False Rejection Rate (FRR) %	FRR ≤ 0.02% (Visible Light Facial Authentication)
Biometric Algorithm	
Card Type	ID Card@125 kHz (Standard)
Communication	TCP/IP*1, Wi-Fi (IEEE802.11 b/g/n/ax) @ 2.4 GHz (Optional), Wiegand (Input or Output)*1,
Supported Software	On-Premise & Cloud Based Software: 1. Easy Time Pay (Supports Web Portal & Mobile App) 2. eClock With Admin and ESS
Access Control Interface	RS485 (RS485 Card Reader / Biometric Reader)
Power Supply	DC 12V 3A
Operating Temperature	-5°C to 45°C
Operating Humidity	10% to 90% RH (Non-condensing)
Dimensions	175.00 mm * 84.50 mm * 21.65 mm (L*W*H)
Net Weight	0.264 Kg
Installation	Wall-mount (Compatible with Asia Gang Box / Single Gang Box)
Ingress Protection Rating	IP65 (waterproof and dustproof) ISO14001, ISO9001, CE, FCC, RoHS

Configuration



BEST Protocol



PUSH Protocol

Dimensions (mm)

