



## SC403



RFID



Access

## PROXIMITY TIME ATTENDANCE SYSTEM WITH ACCESS CONTROL

Card Capacity : 30,000

Transaction Storage : 50,000

Card Reader : Yes

CPU : 32 bit High End Microprocessor

FAR :  $\leq 0.0001\%$  / FRR :  $\leq 1\%$

Identification Speed :  $\leq 0.1\text{sec}$

Display : Black & White

Keypad : 4 x 4 Keypads

LED Indicator : Green/Red

Schedule Bell/Speaker : Mini Speaker

Communication : TCP/IP, USB, RS 232, RS485

Power Supply : 12 V DC, 2Amps

Operating Temperature :  $0^{\circ}\text{C}$  to  $45^{\circ}\text{C}$

Operating Humidity : 20% - 80%

Dimension : 143 x 95.5 x 39.5 mm

### Access Control :

Wiegand : In & Out

Relay : Inbuilt relay to communicate with  
locks, Alarms & Door Sensors

Support Fire Alarm : Yes / Door Sensor : Yes

Anti Pass back : yes / Door Bell : Yes

Support exit reader : KR 500E / Exit Button

50 time zones, 5 Groups, 10 time combinations

Battery : No / Card Readers : Yes

### Compatibility :

- Compatible with Multi Door controllers via weigand
- External Speaker output available (Optional)
- External Bulb output available (Optional)

### Compatible Software & SDK

**SmartOffice**  
Time and Attendance Software

- Smart office suite desktop
- Smart office 365 cloud
- SDK for desktop applications
- Web based Device manager/ ePush server using push data. helps developers & integrators
- Supports 3rd party payroll/HRMS/ERP and other applications